

HOTBODIES RACING.COM

GSX-R1000 (07-08) MEGAPHONE EXHAUST

CAREFULLY READ ALL INSTRUCTIONS BEFORE BEGINNING THE INSTALLATION PROCESS! AS WITH ANY PERFORMANCE MODIFICATION, YOU SHOULD ALWAYS CHECK YOUR WARRANTY BEFORE MAKING ANY MODIFICATIONS TO THE EXHAUST CANISTER OR EMISSIONS DEVICES.

HOTBODIES RACING WILL NOT BE HELD RESPONSIBLE FOR ANY MISUSE OR DAMAGES CAUSED BY THE INSTALLATION OF THIS PRODUCT, NOR WILL WE REPLACE ANY STOCK PARTS TO YOUR MOTORCYCLE.

HOTBODIES RACING RECOMMENDS THAT YOU HAVE A PROFESSIONAL MECHANIC PERFORM THIS INSTALLATION. IN ORDER FOR YOU TO GET THE FULL POTENTIAL FOR THIS PRODUCT IT DOES REQUIRE RE-MAPPING OF THE FUEL INJECTION, WE SUGGEST USING A "POWER COMMANDER III" AND HAVING IT PROFESSIONALLY TUNED USING A DYNAMOMETER AND AN EXHAUST GAS ANALYZER.

IF YOU CHOOSE TO "DO-IT-YOURSELF", WHICH WE DON'T RECOMMEND, ALWAYS TAKE APPROPRIATE SAFETY MEASURES WHEN INSTALLING THIS PRODUCT, SUCH AS SAFETY GOGGLES AND LEATHER GLOVES.



- 1) Remove the stock exhaust canisters on both sides of the motorcycle.
- 2) Position both rearsets to the TOP and FORWARD positions as possible for best fitment of megaphone exhaust.
- 3) Install the megaphones on both sides and make sure both sides are lined up equally. On the left side of the exhaust, make sure it is positioned away from shifter linkage to allow for normal shifting. The rubber boot on the linkage may be in contact with the exhaust, this is ok. MAKE SURE CHAIN IS PROPERLY ADJUSTED.
- 4) Use the provided clamps to fasten the exhaust to the bike, all hardware should be securely fastened and tightened. Your done!

READ CAREFULLY BEFORE INSTALLATION! This exhaust like all after market exhausts has been designed for off road racing use only, and has not been presented for D.O.T. certification! Hotbodies Racing Inc., our distributors, and our dealers will NOT be responsible for the use or misuse of this product. Always check with your local Department of Motor Vehicles before modifying any aspect of your motorcycle.