



12925 Brookprinter Place, Bldg. 400  
Poway, CA 92064

800 555 2805  
858 486 3838

## GSXR 1000 05-08

No Cut Frame Slider

KR TUNED RECOMMENDS THAT YOU HAVE A PROFESSIONAL MECHANIC PERFORM THIS INSTALLATION. IF YOU CHOOSE THE "DO-IT-YOURSELF" METHOD ALWAYS TAKE APPROPRIATE SAFETY MEASURES WHEN INSTALLING THIS PRODUCT. ALWAYS USE SAFETY GOGGLES AND LEATHER GLOVES. CAREFULLY READ ALL INSTRUCTIONS BEFORE BEGINNING THE INSTALLATION PROCESS. IF IN DOUBT, CALL FOR ADDITIONAL HELP BEFORE BEGINNING PROCESS.

**KR TUNED WILL NOT REPLACE ANY PART OF YOUR MOTORCYCLE FOR ANY REASON! MEASURE TWICE, CUT ONCE AND ALWAYS PROPERLY TIGHTEN BOLTS.**



**1.** Identify left side frame slider and bolt. The left slider is longer than the right. Remove left side engine mounting bolt using an 8mm allen wrench.



**2.** Install left side frame slider using new engine mount bolt supplied. Install with flat notch facing towards the body panel. Tighten bolt to manufacturers torque specification.



**3.** Loosen pinch bolt, remove the right side engine mounting bolt. Install right slider using the remaining bolt provided. Tighten engine mount bolt first and then pinch bolt. Tighten both bolts to manufactures torque specification.

---

READ CAREFULLY BEFORE INSTALLATION! These frame sliders have been designed to minimize damage to your motorcycles frame in the event of a crash. KR Tuned cannot guarantee they will protect your motorcycle from any extent of damage as every crash is different and unpredictable. KR Tuned, our distributors, and our dealers will NOT be responsible for the use or misuse of this product or replacing any part of your motorcycle. Always check with your local dealer before modifying any aspect of your motorcycle.

---