

# HOTBODIES RACING.COM

## GSX-R HUGGERS

**(GSX-R1000 05-06', GSX-R600/750 06-07',  
GSX-R1000 07-08',GSX-R 600/750 08-09')**

**HOTBODIES RACING RECOMMENDS THAT YOU HAVE A PROFESSIONAL MECHANIC PERFORM THIS INSTALLATION. IF YOU CHOOSE TO "DO-IT-YOURSELF" ALWAYS TAKE APPROPRIATE SAFETY MEASURES WHEN INSTALLING THIS PRODUCT. CAREFULLY READ ALL INSTRUCTIONS BEFORE BEGINNING THE INSTALLATION PROCESS!**



**1)** Place motorcycle on rear tire stand that elevates rear tire off the ground. Loosen axle nut from rear axle and pull off chain and set to the side of swingarm.



**2)** Pull rear tire back or you can also remove rear tire completely by removing the rear tire axle. Save all bolts and rear axle settings for reinstallation.



**3)** Remove stock hugger from stock mounting points. Save all bolts for reinstall of Hotbodies hugger.



**4)** Install Hotbodies hugger using all stock bolts from stock hugger. Re-install rear tire and chain, make sure to properly adjust your chain. Tighten all hardware and torque axle nut to manufacturer specs and you're done!

**READ CAREFULLY BEFORE INSTALLATION!** This undertail like all undertails has been designed for off road racing use only, and has not been presented for D.O.T. certification! Hotbodies Racing Inc., our distributors, and our dealers will NOT be responsible for the use or misuse of this product. Always check with your local Department of Motor Vehicles before modifying any aspect of your motorcycle.